

AT-LPW30TK

MANUAL BELT-DRIVE WOOD BASE TURNTABLE

Designed for optimal high-fidelity audio reproduction from vinyl.

Developed in Tokyo, Japan with over 50 years of expertise in creating high-fidelity equipment, the LPW30TK turntable is designed to give you optimal high-fidelity audio reproduction from vinyl.

Product Highlights

- Optimal high-fidelity audio experience.
- Teak effect wood veneer finish.
- Connect directly to speakers at home with the built-in preamplifier.
- Fully manual, belt-drive operation with two speeds: 331/3 and 45 RPM.
- Adjustable dynamic anti-skate control.
- Professional anti-resonance, die-cast aluminum platter with rubber mat.
- AT-HS4 headshell and AT-VM95C Dual Moving Magnet phono cartridge with 0.6 mil conical stylus.
- AT-VM95C cartridge is compatible with any VM95 Series replacement stylus, offering a wide choice of options for every application.
- Straight tonearm with hydraulically damped lift control and lockable rest.



SRP: £269.00/€299,00 (inc. VAT)

Specifications

| _ | | | | | |
|-----|--------|---|----|---|-----|
| - 1 | PI | n | ŀ٩ | h | le. |
| | | | | | |

| Drive Method | Belt-drive |
|---------------------------|---|
| Туре | 2-speed, fully manual operation |
| Motor | DC servo motor |
| Speeds | 33⅓ RPM, 45 RPM |
| Turntable Platter | Die-cast aluminum |
| Wow and Flutter | < 0.15% WRMS (33RPM) at 3kHz |
| Signal-to-Noise Ratio | > 60dB |
| Output Level | Pre-amp: PHONO: 4.0mV nominal at 1kHz, 5cm/sec Pre-amp: LINE: 200mV nominal at 1kHz, 5cm/sec |
| Power Supply Requirements | 100 to 240V, 50/60Hz |
| Power Consumption | 220V 50Hz (EU) Working: 1.2W ◆ Motor off: 1.1W ◆ Power Off: 0.2W |
| Dimensions | 116.9 x 420.0 x 340.0 (H x W x Dmm) |
| Weight | 5.0 kg |
| Accessories Included | AT-HS4SV Headshell AT-VM95C Dual Moving Magnet Cartridge with Elliptical Stylus Detachable RCA output cable (dual RCA male to dual RCA male) AC adapter, 45 RPM adapter, Counterweight, Rubber mat, Removable hinged dust cover |



| Model | AT-VM95C |
|-------------------------------|-----------------------------|
| Туре | VM Dual Magnet |
| Output Voltage | 4mV (at 1.5kHz, 5cm/sec) |
| Vertical Tracking Force Range | 1.8 to 2.2g (standard 2.0g) |
| Stylus Shape | Bonded Conical Stylus |
| Stylus Size | 0.6 mil |
| Recommended Load Impedance | 47,000 ohms |
| Weight | 6.1g |
| Replacement Stylus | AT-VMN95C |

Headshell

| Model | AT-HS4SV |
|--------|------------------------|
| Weight | 8.5g |
| Body | Die-cast aluminum body |

| ionearm | |
|----------------------------------|---|
| Туре | Static balanced straight aluminium tonenarm |
| Effective Length | 223.6mm |
| Overhang | 18.6mm |
| Maximum Tracking Error Angle | Less than 2 degrees |
| Stylus Pressure Adjustment Range | 0 to 3g |

