

TECHNICAL SPECIFICATIONS

Connections

Audio Outputs

- (2) XLR outputs (master left/right, balanced)
- (1) RCA output pair (master left/right, unbalanced)
- (2) XLR outputs (booth left/right, balanced)
- (2) XLR outputs (zone left/right, balanced)
- (1) 1/4" (6.35mm) stereo output (headphones)
- (1) 1/8" (3.5mm) stereo output (headphones)

Audio Inputs

- (2) RCA input pairs (line-level, unbalanced)
- (2) RCA input pairs (phono- or line-level, unbalanced)
- (2) XLR+1/4" (6.35mm) input

Other

- (4) USB ports (for USB drives, 5V, 1A)
 - (1) USB port (to computer)
 - (1) Ethernet port
 - (1) IEC power cable input
-

Audio

Main Outputs

- Frequency Response: 20 Hz – 20 kHz +/- 1 dB
- Dynamic Range: > 117 dB (A-weighted)
- Signal-to-Noise Ratio: > 93 dB (A-weighted)

Headroom

- Line Input: > 15 dB
- Mic Inputs: > 20dB
- Outputs: > 20 dB

Channel Separation: < -90 dB (1 kHz, unity)

T.H.D.

- Line/Phono: < 0.01% (1 kHz, unity)
- Microphone: < 0.02% (1 kHz, unity)

Analog Input

- Microphone: -40 dBu (unity) / -60 dBu (minimum)
- Line: +15dBV (minimum) / 0dBV (maximum)

Analog Output

- Main, Balanced: +20 dBu (maximum) / +4 dBu (unity)
 - Main, Unbalanced: +20 dBu (maximum) / 0 dBu (unity)
 - Zone, Balanced: +24 dBu (maximum) / +4 dBu (unity)
 - Booth: +24 dBu (maximum) / +4 dBu (unity)
 - Headphone Output: < 150 mW
-

Power	Connection: IEC Voltage: 100–240VAC, 50/60Hz Consumption: 38W~39W
Dimensions (width x depth x height)	Width x Depth x Height: 28.68 x 19.56 x 4.08" / 5728.47 x 496.82 x 103.63mm
Weight	21.34 lb. 9.7kg

Specifications are subject to change without notice