



CRISEIDE L

FCRLBE1 - NEW-BEIGE

TECHNICAL DATA

Installation: Interno _ Lampada da tavolo

Source: Led integrato

Power: 30W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ Push incluso

Lumen: 1400lm

Color Temperature: 3000K

Light Beam: 360° _ Diffusa

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Energy Class: E

Volume: 0,0480m3

Net Weight: 2.6 kg

Lume con struttura in alluminio. Finitura in new beige. Diffusore in silicone bianco opale. L'appliche è dotato di sorgente luminosa in biemissione led dimmerabile tramite pulsante installato su rosone. Il lume è dotato di sorgente luminosa in biemissione led dimmerabile tramite pulsante installato sulla base. trasformatore incluso.

Lamp with aluminium structure. New beige finish. White opal silicone diffuser. The wall light is equipped with a bi-emission LED light source that can be dimmed by means of a button installed on the rosette. The lume is equipped with a bi-emission LED light source dimmable by means of a button installed on the base. transformer included.

Lampe avec structure en aluminium. Finition en nouveau beige. Diffuseur en silicone opale blanc. L'applique est équipée d'une source lumineuse LED bi-émission qui peut être graduée au moyen d'un bouton installé sur la rosace. Le luminaire est équipé d'une source lumineuse LED bi-émission graduable à l'aide d'un bouton installé sur la base. transformateur inclus.

Lampe mit Aluminiumstruktur. Ausführung in New Beige. Die Wandleuchte ist mit einer bi-emittierenden LED-Lichtquelle ausgestattet, die über einen an der Rosette angebrachten Knopf gedimmt werden kann. Die Leuchte ist mit einer bi-emittierenden LED-Lichtquelle ausgestattet, die über einen am Sockel installierten Taster dimmbar ist. Transformator inklusive.

