



AELA P/M

FAEPBE2 - NEW-BEIGE

TECHNICAL DATA

Installation: Interno _ Lampada a soffitto

Source: Led Integrato

Power: 50W+10W

Power Supply: 220-240V AC _ 50/60Hz

Dimming: Dimmerabile _ taglio fase+push non incl.

Lumen: 3100-3200lm

Color Temperature: 3000K-4000K

Light Beam: 120° _ Biemissione

CRI: >80

Lifespan: 30.000h

IP Rating: IP20

Insulation Class: I

Energy Class: D

Volume: 0,0369m3

Net Weight: 4.8 kg

Montatura in alluminio new beige. Diffusore in metacrilato bianco opale. Sorgente luminosa in biemissione led dimmerabile a taglio di fase tramite dimmer esterno+push (non inclusi).

New Beige aluminium mount. White opal methacrylate di fuser. Dimmable bi emission LED light source with phase cut via an external dimmer + push (not included).

Monture en aluminium nouveau beige. Diffuseur en méthacrylate blanc opale. Source lumineuse en LED bi-émission dimmable en coupure de phase au moyen d'un variateur externe+poussoir (pas inclus).

Neuem Beige Aluminiumrahmen. Opalweißer Methacrylat-Diffusor. Lichtquelle in Bi-Emissions-LED dimmbar in Phase geschnitten durch einen externen Dimmer + Push (nicht enthalten).

